

Spiral cables | 24 V



Art.-No.	Description
	Electrical coil 15-core <ul style="list-style-type: none"> · 3 x 2,5 mm² + 12 x 1,5 mm² · Working length: 3,5 m · External diameter: 75 mm · With 2 plugs 15-pin ISO 12098 · Material: PUR · Retractable properties in accordance with OEM requirements
788 700 100	With clamped cable joint
788 710 100	With anti-kink protection and trumpet cap

Art.-No.	Description
	Electrical coil EBS, 7-core <ul style="list-style-type: none"> · 2 x 4 mm² + 3 x 1,5 mm² + 1 x (2 x 1,5 mm²) · Working length: 3,5 m · External diameter: 55 mm · With 2 EBS plugs ISO 7638 · Additional twisted data pair · Material: PUR · Retractable properties in accordance with OEM requirements
788 600 500	With clamped cable gland
788 610 500	With anti-kink protection and trumpet cap



Art.-No.	Description
	Electrical coil ABS, 5-core <ul style="list-style-type: none"> · 2 x 4 mm² + 3 x 1,5 mm² · Working length: 3,5 m · External diameter: 55 mm · With 2 ABS plugs ISO 7638 · Material: PUR · Retractable properties in accordance with OEM requirements
788 600 400	With clamped cable joint
788 610 400	With anti-kink protection and trumpet cap