



Spiral cables | 24 V

Art.-No.	Description
	Electrical coil 2 x 7-core <ul style="list-style-type: none"> · 6 x 1 mm² + 1 x 1,5 mm² per coil · Working length: 3,5 m · External diameter: 45 mm · With 1 x 15-pin plug and 2 x 7-pin plug Type N/S · Material: PUR · Retractable properties in accordance with OEM requirements
788 900 300	Injected plastic plugs, 9 cores connected
788 900 200	Injected plastic plugs, 12 cores connected
788 900 100	Injected plastic plugs, 13 cores connected
788 700 100	Metal plugs, 9 cores connected
788 700 210	Metal plugs, 12 cores connected
788 700 200	Metal plugs, 13 cores connected



Art.-No.	Description
788 700 500	Short adapter 24 V <ul style="list-style-type: none"> · Towing vehicle: 15 pin ISO 12098; Trailer: 7-pin ISO 1185 and 3731 · Material: PA6 GF30 · Contact allocation: 9-cores · Plug 15-pin, ISO 12098 · Socket 7-pin, Type N, ISO 1185 · Socket 7-pin, Type S, ISO 3731
... .. 1	Individual packaging short adapter

Art.-No.	Description
788 700 600	Short adapter 24 V <ul style="list-style-type: none"> · Towing vehicle: 15 pin ISO 12098; Trailer: 7-pin ISO 1185 and 3731 · Material: PA6 GF30 · Contact allocation: 13-cores · Plug 15-pin, ISO 12098 · Socket 7-pin, Type N, ISO 1185 · Socket 7-pin, Type S, ISO 3731

... .. 1	Individual packaging short adapter
----------	------------------------------------

